



Precision Rated Optics

Work with a PRO!

FiberOpticPRO.com

OFL-301A Optical Fault Locator



The OBL-201A and OFL-301A are a high performance optical fiber troubleshooter for locating fiber breaks and imperfections. It detects the break location in the optical fiber and displays the result on the LCD screen. This portable and easy to use device is an ideal instrument for fiber cable construction and maintenance.

Applications:

- FTtx fiber certification
- CATV technicians (Field verification of fiber continuity)
- MDU installation (Verification of fiber continuity)
- Any application where affordable, "distance to break" testing is required

Features

- Short Dead Zone 3m
- Backlight for easy operation in low light
- Rechargeable batteries
- Data transfer via USB interface
- Interchangeable (SC/ST/SC) connectors

OFL-301A:

Programmed to find multiple faults at a time

Standard Accessories

Rechargeable NiHM battery(4 pcs), AC adapter, PC software and USB cable, travel bag, test report, and manual.

OPTIONAL ACCESSORIES

PRO-CT-001	Fiber Optic Cleaning Cassette
PRO-CT-004	Cleaning Cassette Replacement Reel
VFL-10	650nm Pocket Visual Fault Locator
9392	IBC Cleaner (2.5mm) Cleaning Tool
9393	IBC Cleaner (1.25mm) Cleaning Tool

SPECIFICATIONS

Item / Model No.	OFL - 301A	OBL - 201A
Fiber Type	9/125 μ m Single Mode	
Wavelength	1550 \pm 20 nm	
Emitter Type	LD	
Connector Type	FC/SC/ST	FC/PC (interchangeable SC,ST)
Pulse Width	10ns/20ns/40ns/80ns/160ns/320ns/640ns/1280ns/2560ns/5120ns/12400ns/24800ns (auto-switch)	
Max. Output Power	100 mW	
Max. Measurement Range	130 Km	
Distance Accuracy	+/- (0.8 m + 0.001% x Distance)	
Data Storage	999 Measurements	
Event Dead Zone	3 m	
Power Supply	AC/DC adapter & Rechargeable batteries 4	
Battery Life	15,000 times measurement	
Operating Temp.	14~122 °F (-10 ~ +50 °C)	
Storage Temp.	-4 ~ 140 °F (20 ~ +60 °C)	
Humidity	0 ~ 85% (non-condensing)	
Communication Port	Mini USB	
Weight	10 oz. (286 g)	
Dimension	7.5 x 4.1 x 2.1 in (190 x 105 x 55 mm)	